




FX-SS RANGE STAIN LESS STEEL FLOOR STANDING ENCLOSURE



Lifting hooks



Concealed hinges




Polyurethane gasket



Gutter for better ingress protection



Bracket for cable management



Door earthed to the enclosure



GI Mounting plate

FX-SS RANGE STAIN LESS STEEL FLOOR STANDING ENCLOSURES



CUBICON FX-SS range Stainless Steel Floor Standing Enclosures are renowned for its build quality, aesthetics and functionality. They are designed to protect the equipment in extreme wet and humid conditions.

Specifications and features:

Made from 1.5mm, 304, 316, or 316L stainless steel.

Fully welded mono-block construction-**IP66 rating**.

Right hinged is the default position for single door enclosures.

Door earthed to cabinet via earth studs.

Polyurethane door seal/gasket.

GI mounting plate as a standard for all enclosures.

Z brackets provided to manage the cables on the door.

Folded gutter to ensure effective door seal.

Doors are fitted with concealed hinges and 3point locks.

Enclosures are provided with Lifting hooks & Plinth can be provided as extra

Part Reference	Height	Width	Depth	No. of Doors
FX SS-14840	1400	800	400	1
FX SS-141040	1400	1000	400	1
FX SS-141040D	1400	1000	400	2
FX SS-141240D	1400	1200	400	2
FX SS-16840	1600	800	400	1
FX SS-161040	1600	1000	400	1
FX SS-161040D	1600	1000	400	2
FX SS-161240D	1600	1200	400	2
FX SS-18840	1800	800	400	1
FX SS-181040	1800	1000	400	1
FX SS-181040D	1800	1000	400	2
FX SS-181240D	1800	1200	400	2
FX SS-18850	1800	800	500	1
FX SS-181050	1800	1000	500	1
FX SS-181050D	1800	1000	500	2
FX SS-181250D	1800	1200	500	2
FX SS-20660	2000	600	600	1
FX SS-20860	2000	800	600	1
FX SS-201060	2000	1000	600	1
FX SS-201060D	2000	1000	600	2
FX SS-201260D	2000	1200	600	2